

What Should We Do with Radioactive Waste?

Andrew Cliffe

School of Mathematical Sciences
University of Nottingham

Simulation of Flow in Porous Media and
Applications in Waste Management
and CO₂ Sequestration

**Radon Special Semester 2011 on
Multiscale Simulation & Analysis in Energy and the
Environment**

4th October 2011

Collaborators and Acknowledgements

- ▶ Ian Dryden, Minho Park, Nicola Stone
University of Nottingham, School of Mathematical Sciences
- ▶ Ingolf Busch, Oliver Ernst, Björn Sprunk
TU Freiberg, Institute of Numerical Analysis and
Optimization
- ▶ Gerald van den Bogaart, Silke Konsulke
TU Freiberg, Institute of Stochastics
- ▶ Rob Scheichl, Elisabeth Ullmann
University of Bath, Department of Mathematical Sciences



- ▶ Radioactive waste disposal
- ▶ Treatment of uncertainty
- ▶ Case study - WIPP
- ▶ Conclusions

Radioactive waste disposal

- ▶ Radioactive waste is waste that contains significant amounts of radioactive material.

Radioactive waste disposal

- ▶ Radioactive waste is waste that contains significant amounts of radioactive material.
- ▶ Most radioactive waste comes from the civil nuclear power industry.

Radioactive waste disposal

- ▶ Radioactive waste is waste that contains significant amounts of radioactive material.
- ▶ Most radioactive waste comes from the civil nuclear power industry.
- ▶ Other sources include: military, medical establishments, non-nuclear industries (such the oil industry) and educational and research establishments.

Radioactive waste disposal

- ▶ Radioactive waste is waste that contains significant amounts of radioactive material.
- ▶ Most radioactive waste comes from the civil nuclear power industry.
- ▶ Other sources include: military, medical establishments, non-nuclear industries (such the oil industry) and educational and research establishments.
- ▶ **Whatever your attitude to nuclear power, the existing waste has to be disposed of safely!**

- ▶ Total waste from UK civil nuclear power (assuming no new build):

Radioactive waste disposal

- ▶ Total waste from UK civil nuclear power (assuming no new build):
- ▶ HLW - highly radioactive, heat generating ($\approx 1,300\text{m}^3$).

Radioactive waste disposal

- ▶ Total waste from UK civil nuclear power (assuming no new build):
- ▶ HLW - highly radioactive, heat generating ($\approx 1,300\text{m}^3$).
- ▶ ILW - intermediate radioactivity, not heat generating ($\approx 220,000\text{m}^3$).

Radioactive waste disposal

- ▶ Total waste from UK civil nuclear power (assuming no new build):
- ▶ HLW - highly radioactive, heat generating ($\approx 1,300\text{m}^3$).
- ▶ ILW - intermediate radioactivity, not heat generating ($\approx 220,000\text{m}^3$).
- ▶ LLW - slightly radioactive ($\approx 2,100,000\text{m}^3$).

Radioactive waste disposal

- ▶ Total waste from UK civil nuclear power (assuming no new build):
- ▶ HLW - highly radioactive, heat generating ($\approx 1,300\text{m}^3$).
- ▶ ILW - intermediate radioactivity, not heat generating ($\approx 220,000\text{m}^3$).
- ▶ LLW - slightly radioactive ($\approx 2,100,000\text{m}^3$).
- ▶ All the waste would fill just over half of the new Wembley Stadium ($4,000,000\text{m}^3$).

Radioactive waste disposal

- ▶ Total waste from UK civil nuclear power (assuming no new build):
- ▶ HLW - highly radioactive, heat generating ($\approx 1,300\text{m}^3$).
- ▶ ILW - intermediate radioactivity, not heat generating ($\approx 220,000\text{m}^3$).
- ▶ LLW - slightly radioactive ($\approx 2,100,000\text{m}^3$).
- ▶ All the waste would fill just over half of the new Wembley Stadium ($4,000,000\text{m}^3$).
- ▶ The HLW and ILW would stand approximately 17m deep on the pitch, with the HLW 10 cms deep.

Radioactive waste disposal - issues

- ▶ Some general principles governing management and disposal of radioactive waste:

Radioactive waste disposal - issues

- ▶ Some general principles governing management and disposal of radioactive waste:
- ▶ Some radionuclides have long half-lives and remain dangerous for thousands of years

Radioactive waste disposal - issues

- ▶ Some general principles governing management and disposal of radioactive waste:
- ▶ Some radionuclides have long half-lives and remain dangerous for thousands of years
- ▶ Each country is responsible for dealing with its own waste (no export of waste)

Radioactive waste disposal - issues

- ▶ Some general principles governing management and disposal of radioactive waste:
- ▶ Some radionuclides have long half-lives and remain dangerous for thousands of years
- ▶ Each country is responsible for dealing with its own waste (no export of waste)
- ▶ Minimal assumptions about future development of human society (e.g. can not assume there will be a cure for cancer or other diseases caused by exposure to radioactivity)

Radioactive waste disposal - issues

- ▶ Some general principles governing management and disposal of radioactive waste:
- ▶ Some radionuclides have long half-lives and remain dangerous for thousands of years
- ▶ Each country is responsible for dealing with its own waste (no export of waste)
- ▶ Minimal assumptions about future development of human society (e.g. can not assume there will be a cure for cancer or other diseases caused by exposure to radioactivity)
- ▶ Do not leave a legacy of hazardous and dangerous waste for future generations to manage

Radioactive waste disposal - options

- ▶ Surface storage

Radioactive waste disposal - options

- ▶ Surface storage
- ▶ Disposal at sea

Radioactive waste disposal - options

- ▶ Surface storage
- ▶ Disposal at sea
- ▶ Space disposal

Radioactive waste disposal - options

- ▶ Surface storage
- ▶ Disposal at sea
- ▶ Space disposal
- ▶ Transmutation

Radioactive waste disposal - options

- ▶ Surface storage
- ▶ Disposal at sea
- ▶ Space disposal
- ▶ Transmutation
- ▶ Deep geological disposal

Radioactive waste disposal - options

- ▶ Surface storage
- ▶ Disposal at sea
- ▶ Space disposal
- ▶ Transmutation
- ▶ Deep geological disposal
 - ▶ Repository deep underground in a stable geological formation

Radioactive waste disposal - options

- ▶ Surface storage
- ▶ Disposal at sea
- ▶ Space disposal
- ▶ Transmutation
- ▶ Deep geological disposal
 - ▶ Repository deep underground in a stable geological formation
 - ▶ Multiple barriers - mechanical, chemical, physical

Radioactive waste disposal - options

- ▶ Surface storage
- ▶ Disposal at sea
- ▶ Space disposal
- ▶ Transmutation
- ▶ Deep geological disposal
 - ▶ Repository deep underground in a stable geological formation
 - ▶ Multiple barriers - mechanical, chemical, physical
 - ▶ Accepted as the long-term solution in the UK (2006)

Radioactive waste disposal - options

- ▶ Surface storage
- ▶ Disposal at sea
- ▶ Space disposal
- ▶ Transmutation
- ▶ Deep geological disposal
 - ▶ Repository deep underground in a stable geological formation
 - ▶ Multiple barriers - mechanical, chemical, physical
 - ▶ Accepted as the long-term solution in the UK (2006)
 - ▶ Preferred solution of most countries

- ▶ Assessing the safety of a potential repository is a major scientific undertaking.

Radioactive waste disposal

- ▶ Assessing the safety of a potential repository is a major scientific undertaking.
- ▶ Groundwater pathway - route for radionuclides to get to surface environment.

Radioactive waste disposal

- ▶ Assessing the safety of a potential repository is a major scientific undertaking.
- ▶ Groundwater pathway - route for radionuclides to get to surface environment.
- ▶ Long timescales (many thousands of years) make modelling essential.

Radioactive waste disposal

- ▶ Assessing the safety of a potential repository is a major scientific undertaking.
- ▶ Groundwater pathway - route for radionuclides to get to surface environment.
- ▶ Long timescales (many thousands of years) make modelling essential.
- ▶ Uncertainty is a major issue.

Radioactive waste disposal

- ▶ Assessing the safety of a potential repository is a major scientific undertaking.
- ▶ Groundwater pathway - route for radionuclides to get to surface environment.
- ▶ Long timescales (many thousands of years) make modelling essential.
- ▶ Uncertainty is a major issue.
- ▶ Objective is to make a good decision.

Radioactive waste disposal

- ▶ Assessing the safety of a potential repository is a major scientific undertaking.
- ▶ Groundwater pathway - route for radionuclides to get to surface environment.
- ▶ Long timescales (many thousands of years) make modelling essential.
- ▶ Uncertainty is a major issue.
- ▶ Objective is to make a good decision.
- ▶ NB: Not necessarily interested in the worst possible case.

As we know, there are known knowns. There are things we know we know. We also know there are known unknowns. That is to say we know there are some things we do not know. But there are also unknown unknowns, the ones we don't know we don't know.

Donald Rumsfeld

Five-fold strategy for dealing with uncertainty (Bailey 2005):

Five-fold strategy for dealing with uncertainty (Bailey 2005):

1. No impact on safety

Five-fold strategy for dealing with uncertainty (Bailey 2005):

1. No impact on safety
 - ▶ eg. sorption coefficient for short lived radionuclides

Five-fold strategy for dealing with uncertainty (Bailey 2005):

1. No impact on safety
 - ▶ eg. sorption coefficient for short lived radionuclides
2. Bounding uncertainty

Five-fold strategy for dealing with uncertainty (Bailey 2005):

1. No impact on safety
 - ▶ eg. sorption coefficient for short lived radionuclides
2. Bounding uncertainty
 - ▶ eg. solubility limit

Five-fold strategy for dealing with uncertainty (Bailey 2005):

1. No impact on safety
 - ▶ eg. sorption coefficient for short lived radionuclides
2. Bounding uncertainty
 - ▶ eg. solubility limit
3. Excluding uncertainty

Five-fold strategy for dealing with uncertainty (Bailey 2005):

1. No impact on safety
 - ▶ eg. sorption coefficient for short lived radionuclides
2. Bounding uncertainty
 - ▶ eg. solubility limit
3. Excluding uncertainty
 - ▶ eg. meteorite impact

Five-fold strategy for dealing with uncertainty (Bailey 2005):

1. No impact on safety
 - ▶ eg. sorption coefficient for short lived radionuclides
2. Bounding uncertainty
 - ▶ eg. solubility limit
3. Excluding uncertainty
 - ▶ eg. meteorite impact
4. Explicit quantification

Five-fold strategy for dealing with uncertainty (Bailey 2005):

1. No impact on safety
 - ▶ eg. sorption coefficient for short lived radionuclides
2. Bounding uncertainty
 - ▶ eg. solubility limit
3. Excluding uncertainty
 - ▶ eg. meteorite impact
4. Explicit quantification
 - ▶ eg. travel times in the groundwater pathway

Five-fold strategy for dealing with uncertainty (Bailey 2005):

1. No impact on safety
 - ▶ eg. sorption coefficient for short lived radionuclides
2. Bounding uncertainty
 - ▶ eg. solubility limit
3. Excluding uncertainty
 - ▶ eg. meteorite impact
4. Explicit quantification
 - ▶ eg. travel times in the groundwater pathway
5. Stylised approach

Five-fold strategy for dealing with uncertainty (Bailey 2005):

1. No impact on safety
 - ▶ eg. sorption coefficient for short lived radionuclides
2. Bounding uncertainty
 - ▶ eg. solubility limit
3. Excluding uncertainty
 - ▶ eg. meteorite impact
4. Explicit quantification
 - ▶ eg. travel times in the groundwater pathway
5. Stylised approach
 - ▶ eg. biosphere (ICRP and IAEA projects)

Case study - WIPP

- WIPP - Waste Isolation Pilot Plant.




Figure: Cross section through the rock at the WIPP site

Case study - WIPP

- ▶ WIPP - Waste Isolation Pilot Plant.
- ▶ US DOE repository for radioactive waste situated in New Mexico.




Figure: Cross section through the rock at the WIPP site

Case study - WIPP

- ▶ WIPP - Waste Isolation Pilot Plant.
- ▶ US DOE repository for radioactive waste situated in New Mexico.
- ▶ Located at a depth of 655m within bedded evaporites, primarily halite.




Figure: Cross section through the rock at the WIPP site

Case study - WIPP

- ▶ WIPP - Waste Isolation Pilot Plant.
- ▶ US DOE repository for radioactive waste situated in New Mexico.
- ▶ Located at a depth of 655m within bedded evaporites, primarily halite.
- ▶ The most transmissive rock in the region is the Culebra dolomite.




Figure: Cross section through the rock at the WIPP site

Case study - WIPP

- ▶ WIPP - Waste Isolation Pilot Plant.
- ▶ US DOE repository for radioactive waste situated in New Mexico.
- ▶ Located at a depth of 655m within bedded evaporites, primarily halite.
- ▶ The most transmissive rock in the region is the Culebra dolomite.
- ▶ Culebra would be the principal pathway for transport of radionuclides away from the repository in the event of an accidental breach.






Figure: Cross section through the rock at the WIPP site

Case study - WIPP




- Region containing data is 20km by 30km with the WIPP repository in the centre.

Case study - WIPP



- ▶ Region containing data is 20km by 30km with the WIPP repository in the centre.
- ▶ Measurements of transmissivity, T , and freshwater head, h , are available at 39 locations.

Case study - WIPP



- ▶ Region containing data is 20km by 30km with the WIPP repository in the centre.
- ▶ Measurements of transmissivity, T , and freshwater head, h , are available at 39 locations.
- ▶ Measurements are irregularly spaced, most concentrated around the repository in centre of region.

- ▶ One scenario at WIPP is a release of radionuclides by means of a borehole drilled into the repository.

- ▶ One scenario at WIPP is a release of radionuclides by means of a borehole drilled into the repository.
- ▶ Radionuclides are released into the Culebra dolomite and then transported by groundwater.

- ▶ One scenario at WIPP is a release of radionuclides by means of a borehole drilled into the repository.
- ▶ Radionuclides are released into the Culebra dolomite and then transported by groundwater.
- ▶ Flow is two-dimensional to a good approximation.

- ▶ One scenario at WIPP is a release of radionuclides by means of a borehole drilled into the repository.
- ▶ Radionuclides are released into the Culebra dolomite and then transported by groundwater.
- ▶ Flow is two-dimensional to a good approximation.
- ▶ The time taken to travel from the repository to the boundary of the WIPP site is an important quantity.

Case study - WIPP

- ▶ Find $h(x)$ such that:

- Find $h(x)$ such that:

$$\nabla T \nabla h = 0, \quad x \in \mathfrak{D},$$

$$h = h_0, \quad x \in \partial \mathfrak{D},$$

$$T(x_i) = T_i, \quad x_i \in \mathfrak{D}, \quad i = 1, \dots, 39.$$

Case study - WIPP

- Find $h(x)$ such that:

$$\nabla T \nabla h = 0, \quad x \in \mathfrak{D},$$

$$h = h_0, \quad x \in \partial \mathfrak{D},$$

$$T(x_i) = T_i, \quad x_i \in \mathfrak{D}, \quad i = 1, \dots, 39.$$

- Then solve

$$\dot{\zeta} = -\frac{T(\zeta)}{e\phi} \nabla h(\zeta), \quad \zeta(0) = \zeta_0,$$

and compute the time, t_f , at which $\zeta(t) \in \partial \mathfrak{D}_W$, where e is the thickness of the layer, ϕ the porosity and $\partial \mathfrak{D}_W$ is the boundary of the WIPP site.

Case study - WIPP

- Find $h(x)$ such that:

$$\nabla T \nabla h = 0, \quad x \in \mathfrak{D},$$

$$h = h_0, \quad x \in \partial \mathfrak{D},$$

$$T(x_i) = T_i, \quad x_i \in \mathfrak{D}, \quad i = 1, \dots, 39.$$

- Then solve

$$\dot{\zeta} = -\frac{T(\zeta)}{e\phi} \nabla h(\zeta), \quad \zeta(0) = \zeta_0,$$

and compute the time, t_f , at which $\zeta(t) \in \partial \mathfrak{D}_W$, where e is the thickness of the layer, ϕ the porosity and $\partial \mathfrak{D}_W$ is the boundary of the WIPP site.

- Let $s_f = \log(t_f)$.

- ▶ Problem on previous slide is ill-posed since we don't know T for all $x \in \mathcal{D}$.

- ▶ Problem on previous slide is ill-posed since we don't know T for all $x \in \mathcal{D}$.
- ▶ Limited information on the transmissivity leads to uncertainty.

- ▶ Problem on previous slide is ill-posed since we don't know T for all $x \in \mathcal{D}$.
- ▶ Limited information on the transmissivity leads to uncertainty.
- ▶ It is important to understand and quantify the effect of this uncertainty on the results - in particular on the travel time.

- ▶ Problem on previous slide is ill-posed since we don't know T for all $x \in \mathcal{D}$.
- ▶ Limited information on the transmissivity leads to uncertainty.
- ▶ It is important to understand and quantify the effect of this uncertainty on the results - in particular on the travel time.
- ▶ One approach to uncertainty quantification is to use probabilistic techniques.

- ▶ Problem on previous slide is ill-posed since we don't know T for all $x \in \mathcal{D}$.
- ▶ Limited information on the transmissivity leads to uncertainty.
- ▶ It is important to understand and quantify the effect of this uncertainty on the results - in particular on the travel time.
- ▶ One approach to uncertainty quantification is to use probabilistic techniques.
- ▶ Probabilistic solution - distribution function for s_f , $F_{S_f}(s)$.

- ▶ Problem on previous slide is ill-posed since we don't know T for all $x \in \mathcal{D}$.
- ▶ Limited information on the transmissivity leads to uncertainty.
- ▶ It is important to understand and quantify the effect of this uncertainty on the results - in particular on the travel time.
- ▶ One approach to uncertainty quantification is to use probabilistic techniques.
- ▶ Probabilistic solution - distribution function for s_f , $F_{S_f}(s)$.
- ▶ Interpretation of probability is important - a subjective Bayesian approach is used here.

- ▶ Goal is to compute $F_{S_f}(s)$. The following steps are required:

Probabilistic Uncertainty Quantification

- ▶ Goal is to compute $F_{S_f}(s)$. The following steps are required:
- ▶ Step 0 - collect data.

- ▶ Goal is to compute $F_{S_f}(s)$. The following steps are required:
- ▶ Step 0 - collect data.
- ▶ Step 1 - build stochastic model.

- ▶ Goal is to compute $F_{S_f}(s)$. The following steps are required:
- ▶ Step 0 - collect data.
- ▶ Step 1 - build stochastic model.
- ▶ Step 2 - solve the stochastic model.

- ▶ Goal is to compute $F_{S_f}(s)$. The following steps are required:
- ▶ Step 0 - collect data.
- ▶ Step 1 - build stochastic model.
- ▶ Step 2 - solve the stochastic model.
- ▶ Step 3 - post process - calculate the quantities of interest - travel times.

- ▶ Goal is to compute $F_{S_f}(s)$. The following steps are required:
- ▶ Step 0 - collect data.
- ▶ Step 1 - build stochastic model.
- ▶ Step 2 - solve the stochastic model.
- ▶ Step 3 - post process - calculate the quantities of interest - travel times.
- ▶ Step 4 - interpret the results.

- Represent log transmissivity field, $Z = \log(T)$, as a Gaussian random field with mean and covariance:

$$E[Z(\mathbf{x})] = \beta_0 + \beta_1 x_1 + \beta_2 x_2$$

$$\text{Cov}[Z(\mathbf{x}), Z(\mathbf{x}')] = \omega^2 C(\mathbf{x}, \mathbf{x}') = \omega^2 \exp(-\|\mathbf{x} - \mathbf{x}'\|/\lambda) .$$

- ▶ Represent log transmissivity field, $Z = \log(T)$, as a Gaussian random field with mean and covariance:

$$E[Z(\mathbf{x})] = \beta_0 + \beta_1 x_1 + \beta_2 x_2$$

$$\text{Cov}[Z(\mathbf{x}), Z(\mathbf{x}')] = \omega^2 C(\mathbf{x}, \mathbf{x}') = \omega^2 \exp(-\|\mathbf{x} - \mathbf{x}'\|/\lambda).$$

- ▶ The joint probability distribution, $f_{\Theta}(\theta)$, for the hyperparameters

$$\theta = (\beta_0, \beta_1, \beta_2, \omega^2, \lambda)$$

is estimated using a standard Bayesian analysis and MCMC to generate samples of θ drawn from $f_{\Theta}(\theta)$.

Stochastic model for WIPP




Figure: Probability density function for λ from MCMC calculation.

- ▶ The measurements of transmissivity are also used to condition the random field model (so that each realisation agrees with the measured values at the measurement points).

- ▶ The measurements of transmissivity are also used to condition the random field model (so that each realisation agrees with the measured values at the measurement points).
- ▶ This leads to a low-rank modification of the covariance operator (so that the variance is zero at the measurement points).

- ▶ The measurements of transmissivity are also used to condition the random field model (so that each realisation agrees with the measured values at the measurement points).
- ▶ This leads to a low-rank modification of the covariance operator (so that the variance is zero at the measurement points).
- ▶ Note there is uncertainty in the hyperparameters as well as that inherent in the random field model for T .

- ▶ The measurements of transmissivity are also used to condition the random field model (so that each realisation agrees with the measured values at the measurement points).
- ▶ This leads to a low-rank modification of the covariance operator (so that the variance is zero at the measurement points).
- ▶ Note there is uncertainty in the hyperparameters as well as that inherent in the random field model for T .
- ▶ This uncertainty must be taken into account in the analysis.

- ▶ Gaussian RF $Z(x, \omega)$ can be written in the form

$$Z(x, \omega) = z(x) + \sum_{i=1}^{\infty} \sqrt{\lambda_i} \psi_i(x) \xi_i(\omega).$$

where the ξ_i are iid standard normal random variables.

- ▶ Gaussian RF $Z(x, \omega)$ can be written in the form

$$Z(x, \omega) = z(x) + \sum_{i=1}^{\infty} \sqrt{\lambda_i} \psi_i(x) \xi_i(\omega).$$

where the ξ_i are iid standard normal random variables.

- ▶ We have

$$\begin{aligned} \mathbb{E}[Z] &= z(x), \\ \text{Cov}[Z(x), Z(y)] &= \sum_{i=1}^{\infty} \sqrt{\lambda_i \lambda_j} \psi_i(x) \psi_j(y). \end{aligned}$$

[Karhunen, 1947], [Loève, 1948]

Stochastic model for WIPP

- ▶ Gaussian RF $Z(x, \omega)$ can be written in the form

$$Z(x, \omega) = z(x) + \sum_{i=1}^{\infty} \sqrt{\lambda_i} \psi_i(x) \xi_i(\omega).$$

where the ξ_i are iid standard normal random variables.

- ▶ We have

$$\begin{aligned} \mathbb{E}[Z] &= z(x), \\ \text{Cov}[Z(x), Z(y)] &= \sum_{i=1}^{\infty} \sqrt{\lambda_i \lambda_j} \psi_i(x) \psi_j(y). \end{aligned}$$

[Karhunen, 1947], [Loève, 1948]

- ▶ Here $\text{Cov}[Z(x), Z(y)]$ is the covariance function of the conditioned field.

► Solve

$$\begin{aligned}\nabla \cdot [T(x, \xi) \nabla h(x, \xi)] &= 0 & x \in \mathcal{D}, \text{ a.s.} \\ h(x, \xi) &= h_0(x) & x \in \partial\mathcal{D}, \text{ a.s.}\end{aligned}$$

where

$$\log T(x, \xi) = z(x) + \sum_{i=1}^{\infty} \sqrt{\lambda_i} \psi_i(x) \xi_i.$$

- Solve

$$\begin{aligned}\nabla \cdot [T(x, \xi) \nabla h(x, \xi)] &= 0 & x \in \mathcal{D}, a.s. \\ h(x, \xi) &= h_0(x) & x \in \partial\mathcal{D}, a.s.\end{aligned}$$

where

$$\log T(x, \xi) = z(x) + \sum_{i=1}^{\infty} \sqrt{\lambda_i} \psi_i(x) \xi_i.$$

- Compute the log of travel time, s_f , from h and T .

- Solve

$$\begin{aligned}\nabla \cdot [T(x, \xi) \nabla h(x, \xi)] &= 0 & x \in \mathcal{D}, a.s. \\ h(x, \xi) &= h_0(x) & x \in \partial\mathcal{D}, a.s.\end{aligned}$$

where

$$\log T(x, \xi) = z(x) + \sum_{i=1}^{\infty} \sqrt{\lambda_i} \psi_i(x) \xi_i.$$

- Compute the log of travel time, s_f , from h and T .
- Thus s_f depends on ξ and θ , and the problem is to compute the stochastic law of s_f from the joint law of ξ and θ .

- ▶ Taking account of uncertainty in hyperparameters:

Solution of stochastic model

- ▶ Taking account of uncertainty in hyperparameters:
- ▶ Now

$$F_{S_f}(s) = \int_{s_f(\xi, \theta) \leq s} f_{\Xi, \Theta}(\xi, \theta) d\xi d\theta,$$

Solution of stochastic model

- ▶ Taking account of uncertainty in hyperparameters:
- ▶ Now

$$\begin{aligned} F_{S_f}(s) &= \int_{s_f(\xi, \theta) \leq s} f_{\Xi, \Theta}(\xi, \theta) d\xi d\theta, \\ &= \int \left(\int_{s_f(\xi, \theta) \leq s} f_{\Xi|\Theta}(\xi|\theta) d\xi \right) f_{\Theta}(\theta) d\theta, \end{aligned}$$

Solution of stochastic model

- ▶ Taking account of uncertainty in hyperparameters:
- ▶ Now

$$\begin{aligned}F_{S_f}(s) &= \int_{s_f(\xi, \theta) \leq s} f_{\Xi, \Theta}(\xi, \theta) d\xi d\theta, \\&= \int \left(\int_{s_f(\xi, \theta) \leq s} f_{\Xi|\Theta}(\xi|\theta) d\xi \right) f_{\Theta}(\theta) d\theta, \\&= \int F_{S_f|\Theta}(s|\theta) f_{\Theta}(\theta) d\theta.\end{aligned}$$

where

$$F_{S_f|\Theta}(s|\theta) = \int_{s_f(\xi, \theta) \leq s} f_{\Xi|\Theta}(\xi|\theta) d\xi.$$

- ▶ $F_{S_f|\Theta}(s|\theta)$ is obtained from the solution of the stochastic PDE for each value of θ .

Solution of stochastic model

- ▶ $F_{S_f|\Theta}(s|\theta)$ is obtained from the solution of the stochastic PDE for each value of θ .
- ▶ We do not have an explicit expression for $f_{\Theta}(\theta)$, just a (large) sample, $\{\theta_i\}_{i=1}^{N_{\theta}}$, of equally probable values of θ generated by the MCMC calculation.

Solution of stochastic model

- ▶ $F_{S_f|\Theta}(s|\theta)$ is obtained from the solution of the stochastic PDE for each value of θ .
- ▶ We do not have an explicit expression for $f_{\Theta}(\theta)$, just a (large) sample, $\{\theta_i\}_{i=1}^{N_{\theta}}$, of equally probable values of θ generated by the MCMC calculation.
- ▶ Use Monte-Carlo to compute $F_{S_f}(s)$ as

$$F_{S_f}(s) = \frac{1}{N_{\theta}} \sum_{i=1}^{N_{\theta}} F_{S_f|\Theta}(s|\theta_i)$$

where $\{\theta_i\}_{i=1}^{N_{\theta}}$ is the MCMC sample.

- ▶ Probably the most expensive part of the calculation

Solution of the stochastic PDE

- ▶ Probably the most expensive part of the calculation
- ▶ Currently a very active area of research

Solution of the stochastic PDE

- ▶ Probably the most expensive part of the calculation
- ▶ Currently a very active area of research
- ▶ Curse of dimension is the main issue (see later slide)

- ▶ Probably the most expensive part of the calculation
- ▶ Currently a very active area of research
- ▶ Curse of dimension is the main issue (see later slide)
- ▶ Options include:
 - ▶ Brute force Monte-Carlo
 - ▶ Quasi Monte-Carlo methods
 - ▶ Generalised polynomial chaos methods
 - ▶ Multi-level Monte-Carlo methods

- ▶ Probably the most expensive part of the calculation
- ▶ Currently a very active area of research
- ▶ Curse of dimension is the main issue (see later slide)
- ▶ Options include:
 - ▶ Brute force Monte-Carlo
 - ▶ Quasi Monte-Carlo methods
 - ▶ Generalised polynomial chaos methods
 - ▶ Multi-level Monte-Carlo methods
- ▶ Many challenges remain in this area, with several promising lines of research.

- ▶ Truncated KL expansion

$$Z_N(x, \omega) = z(x) + \sum_{i=1}^N \sqrt{\lambda_i} \psi_i(x) \xi_i(\omega).$$

Solution of the stochastic PDE

- ▶ Truncated KL expansion

$$Z_N(x, \omega) = z(x) + \sum_{i=1}^N \sqrt{\lambda_i} \psi_i(x) \xi_i(\omega).$$

- ▶ Solve

$$\begin{aligned} \nabla \cdot [T(x, \xi) \nabla h(x, \xi)] &= 0 & x \in \mathcal{D}, \text{ a.s.} \\ h(x, \xi) &= h_0(x) & x \in \partial\mathcal{D}, \text{ a.s.} \end{aligned}$$

where

$$\log T(x, \xi) = z(x) + \sum_{i=1}^N \sqrt{\lambda_i} \psi_i(x) \xi_i.$$

Solution of the stochastic PDE

- ▶ Truncated KL expansion

$$Z_N(x, \omega) = z(x) + \sum_{i=1}^N \sqrt{\lambda_i} \psi_i(x) \xi_i(\omega).$$

- ▶ Solve

$$\begin{aligned} \nabla \cdot [T(x, \xi) \nabla h(x, \xi)] &= 0 & x \in \mathcal{D}, \text{ a.s.} \\ h(x, \xi) &= h_0(x) & x \in \partial\mathcal{D}, \text{ a.s.} \end{aligned}$$

where

$$\log T(x, \xi) = z(x) + \sum_{i=1}^N \sqrt{\lambda_i} \psi_i(x) \xi_i.$$

- ▶ Compute distribution function for s_f .

Solution of the stochastic PDE

- ▶ How big should N be?

Solution of the stochastic PDE

- How big should N be? Possibly too large for some current methods ..




Figure: Distribution function for the log travel time for various N .

Solution of stochastic model

- ▶ In this work we used a Gaussian process emulator to approximate $F_{S_f|\Theta}(s|\theta)$ by $\tilde{F}_{S_f|\Theta}(s|\theta)$.

Solution of stochastic model

- ▶ In this work we used a Gaussian process emulator to approximate $F_{S_f|\Theta}(s|\theta)$ by $\tilde{F}_{S_f|\Theta}(s|\theta)$.
- ▶ This involves solving the stochastic PDE for a set (Latin hypercube) of values of θ (solves done by brute force for Monte-Carlo).

Solution of stochastic model

- ▶ In this work we used a Gaussian process emulator to approximate $F_{S_f|\Theta}(s|\theta)$ by $\tilde{F}_{S_f|\Theta}(s|\theta)$.
- ▶ This involves solving the stochastic PDE for a set (Latin hypercube) of values of θ (solves done by brute force for Monte-Carlo).
- ▶ (Describing Gaussian process emulators would be another talk - think of them as a way of doing interpolation with scattered data in high dimensions - similar to RBF methods.)

Solution of stochastic model

- ▶ In this work we used a Gaussian process emulator to approximate $F_{S_f|\Theta}(s|\theta)$ by $\tilde{F}_{S_f|\Theta}(s|\theta)$.
- ▶ This involves solving the stochastic PDE for a set (Latin hypercube) of values of θ (solves done by brute force for Monte-Carlo).
- ▶ (Describing Gaussian process emulators would be another talk - think of them as a way of doing interpolation with scattered data in high dimensions - similar to RBF methods.)
- ▶ Then use the emulator to evaluate the sum

$$F_{S_f}(s) = \frac{1}{N_\theta} \sum_{i=1}^{N_\theta} \tilde{F}_{S_f|\Theta}(s|\theta_i)$$

to obtain the required solution.

- ▶ For a given θ the stochastic model gives different realisations of T .

- ▶ For a given θ the stochastic model gives different realisations of T .

(Loading Movie)

- ▶ Different realisations give different pathways and travel times.

- ▶ The distribution function, $F_{S_f}(s)$ contains a description of the uncertainty due to the hyperparameters as well as the uncertainty due to the random field model of transmissivity.

- The distribution function, $F_{S_f}(s)$ contains a description of the uncertainty due to the hyperparameters as well as the uncertainty due to the random field model of transmissivity.




Figure: Distribution function for the log travel time.

- ▶ Radioactive waste disposal is an important problem with many scientific challenges.

- ▶ Radioactive waste disposal is an important problem with many scientific challenges.
- ▶ Characterising and quantifying uncertainty is necessary for the safety assessment of a potential radioactive waste repository.

- ▶ Radioactive waste disposal is an important problem with many scientific challenges.
- ▶ Characterising and quantifying uncertainty is necessary for the safety assessment of a potential radioactive waste repository.
- ▶ Uncertainties in the hyperparameters of the stochastic model for transmissivity can be dealt with in a Bayesian framework.

- ▶ Radioactive waste disposal is an important problem with many scientific challenges.
- ▶ Characterising and quantifying uncertainty is necessary for the safety assessment of a potential radioactive waste repository.
- ▶ Uncertainties in the hyperparameters of the stochastic model for transmissivity can be dealt with in a Bayesian framework.
- ▶ The central computational/mathematical problem is solving elliptic PDEs with random coefficients.

- ▶ Radioactive waste disposal is an important problem with many scientific challenges.
- ▶ Characterising and quantifying uncertainty is necessary for the safety assessment of a potential radioactive waste repository.
- ▶ Uncertainties in the hyperparameters of the stochastic model for transmissivity can be dealt with in a Bayesian framework.
- ▶ The central computational/mathematical problem is solving elliptic PDEs with random coefficients.
- ▶ Exciting and important area of research with many promising approaches.